



Spiral Elbows



Machine-formed Spiral Elbow constructed from G90 galvanized steel coil (26ga), available in a long and short radius. They are designed to fit directly into the pipe with a strengthening bead that creates a consistent stopping point for installs once the sealant is applied. This product maintains a SMACNA leakage rating of .025% and exceeds SMACNA's high velocity, and medium pressure requirements (-2" WG to +10" WG).

Spiral Elbow 1.5 CLR

Drawing	Material Type	Size (inch)	G90/Gauge	B (inch) (1.5xCLR)	C (inch)	Weight (lbs.)
	Galvanized Paint Grip	6	26	9	2-3/8	2.32
		8	26	12	2-3/4	4.08
		10	26	15	3-1/8	6.05
		12	26	18	3-9/16	8.69
		14	26	21	3-15/16	11.67
		16	26	24	4-5/16	17.75
		18	26	27	4-3/4	22.45
		20	26	30	5-1/4	27.52
		22	26	33	5-1/4	32.39
		24	26	36	5-1/4	38.86

Drawing	Material Type	Size (inch)	G90/Gauge	B (inch) (1.5xCLR)	C (inch)	Weight (lbs.)
	Galvanized Paint Grip	6	26	9	2-3/8	1.56
		8	26	12	2-3/4	2.73
		10	26	15	3-1/8	4.05
		12	26	18	3-9/16	5.82
		14	26	21	3-15/16	7.83
		16	26	24	4-5/16	11.90
		18	26	27	4-3/4	15.05
		20	26	30	5-1/4	18.44
		22	26	33	5-1/4	21.70
		24	26	36	5-1/4	25.84

Spiral Elbow 1.0 CLR

Drawing	Material Type	Size (inch)	G90/Gauge	B (inch) (1.0xCLR)	C (inch)	Weight (lbs.)
	Galvanized Paint Grip	6	26	6	2-3/8	1.97
		8	26	8	2-3/4	3.15
		10	26	10	3-1/8	4.84
		12	26	12	3-9/16	6.74
		14	26	14	3-15/16	9.19
		16	26	16	4-5/16	13.85
		18	26	18	4-3/4	21.38
		20	26	20	5-1/4	25.31
		22	26	22	5-1/4	29.60
		24	26	24	5-1/4	29.60

Drawing	Material Type	Size (inch)	G90/Gauge	B (inch) (1.0xCLR)	C (inch)	Weight (lbs.)
	Galvanized Paint Grip	6	26	6	2-3/8	1.33
		8	26	8	2-3/4	2.11
		10	26	10	3-1/8	3.24
		12	26	12	3-9/16	4.51
		14	26	14	3-15/16	6.16
		16	26	16	4-5/16	9.27
		18	26	18	4-3/4	12.84
		20	26	20	5-1/4	14.33
		22	26	22	5-1/4	16.95
		24	26	24	5-1/4	19.83



2225 Ola Lane | Haltom City, TX 76111
 sales@haltomind.com | phone: 817-770-0811

Connect with the Best